



PS-10T GEOPHONE MAIN SPECIFICATIONS

OVERVIEW

B series geophone has wide frequency band and high spurious frequency.



The tolerance of all parameters is controlled within +/-5%.

B series geophone has good stability, high accuracy and stable signal output.

The unique double coils structure considerably makes the distortion lower.

GEOPHONE SPECIFICATIONS

PS-10T	
Parameter/mode	PS-10T (20°C)
Natural Frequency (Hz)	10 ± 5%
Coil Resistance (Ω)	375 ± 5%
Sensitivity (V/m/s)	28.8 ± 5%
Sensitivity With Shunt Resistor (V/m/s)	22.5 ± 5% (1339 Ω)
Open circuit damping	0.25 ± 5%
Damping with Shunt Resistor	0.60 ± 5% (1339 Ω)
Distortion (%)	≤0.2
Spurious Frequency (Hz)	≥340
Max. Motion (mm)	2
Moving Mass (g)	11
Dimensions (dxh) mm	25.4 x 32
Temperature Range (°C)	-40° to 70°C
Warranty Period(Year)	2
Weight (g)	75



CONTACT

Netherlands - The Hague
 Diederik Schrijvers
 Mobile: +31 6 4132 9010
 Email: diederik@vibraphone.nl
 Website: vibraphone.nl

