



---

## PS-2/260 GEOPHONE MAIN SPECIFICATIONS

---

### OVERVIEW

PS-2/260 geophone is a low frequency geophone developed following request of seismic exploration and engineering which is mainly to receive deep level, low frequency and weak signal. It can be used as single point and also 3-component

### FEATURES


- Low Frequency: 2 Hz
- High Sensitivity: 260 V/m/s
- High SNR and wide dynamic range
- Vertical and horizontal are available

---

## GEOPHONE SPECIFICATIONS

---

PS-2/260	
Parameter/mode	PS-2/260 (20°C)
Natural Frequency (Hz)	2 ±15 %
Coil Resistance (Ω)	6400 ± 10%
Sensitivity (V/m/s)	260 ± 15%
Damping	0.65 ± 15%
Distortion (%)	≤0.3
Spurious Frequency (Hz)	≥120
Moving Mass (g)	60
Dimensions (d×h) mm	38.5 × 46
Temperature Range (°C)	-40° to 80°C
Warranty Period(Year)	1
Weight (g)	270



## CONTACT

Netherlands - The Hague  
Diederik Schrijvers  
Mobile: +31 6 4132 9010  
Email: [diederik@vibraphone.nl](mailto:diederik@vibraphone.nl)  
Website: [vibraphone.nl](http://vibraphone.nl)

